

TRAY FOR SURGICAL FASTNERS

5 Priority is claimed to Provisional Application Serial
Number 60/234,491 filing date September 22, 2000.

Field of the Invention

10 The present invention relates to an apparatus and method
for applying surgical fasteners, and in one particular aspect
to such an apparatus and method for driving rivets to secure
cranial plates.

Background

15 It is known in the art to apply fasteners for attaching
sutures, bone plates, and connective tissue. The fastener is
20 inserted into a hole in a bone and generally through some
application of force is caused to expand. One particular
method for driving a fastener is disclosed in U.S. Patent No.
5,398,861 by Green which discloses a spring loaded retractable
25 piston and a pivotable trigger device for releasing the piston
and allowing it to drive forward and drive home a fastener.
One disadvantage of this device lies in the difficulty in
grasping the device and firing the trigger simultaneously.

30 To more easily access the fasteners, it would be
desirable to have something which can carry the fasteners to
that they will not fall out and allow easy grasping with the
applier.

Summary of the Invention

35 A tray according to the present invention holds one or
more surgical fasteners. It comprises a base have at least

one well therein, one of the surgical fasteners within the base and a film over the base and the well. Preferably, some treatment of the film at the well is provided to more easily allow an instrument to penetrate the film and access the well to remove the fastener. This could comprise providing an opening through the film such as a slit, or a weakness in the film such as scoring. Preferably, the well and the surgical fastener are sterile. The film thus holds the fastener in the well and maintains the sterility.

A method of holding surgical fasteners according to the present invention comprises the steps of: providing a tray having a base with at least one well therein; providing one of the surgical fasteners in the well; and covering the well with a film. Preferably, the method includes penetrating the film with an instrument and removing the fastener from the well with the instrument, which preferably is an applier for applying the surgical fastener.

Preferably, the method further comprises the step of modifying the film over the well to ease the ability of the instrument to penetrate the well, such as by providing an opening in the film such as a slit, or by providing a weakness such as scoring of the film.

Brief Description of the Drawings

FIG. 1 is a top plan view of an instrument for applying surgical fasteners according to the present invention;

FIG. 2 is a section view taken along lines 2--2 of FIG. 1;

FIG. 3 is a perspective detail view of a release button for the instrument of FIG. 1;

FIG. 4 is perspective view of a fastener for using in the instrument of FIG. 1;

FIG. 5 is a section view taken along lines 5--5 of FIG. 4;

FIG. 6 is a top plan view of a plate to be applied using the fastener of FIG. 4;

FIG. 7 is a top plan view of a tray holding a plurality of the fasteners of FIG. 4;

FIG. 8 is a sectional view taken along lines 8--8 of FIG. 7;

FIG. 9 is a detail sectional view taken along lines 9--9 of FIG. 7;

FIG. 10 is a perspective view of the tray of FIG. 7;

FIG. 11 is a sectional view taken along lines 11--11 of FIG. 1;

FIG. 12 is top plan view of a drill for drilling holes in a skull to receive the fastener of FIG. 4; and

FIG. 13 is a sectional view taken along lines 13--13 of FIG. 12.

Detailed Description

Referring now to the drawings, FIGS. 1 and 2 illustrate a rivet applier 10 according to the present invention. It comprises in general an elongated cylindrical body 12, a piston 14 restrained by a spring 16 and a release mechanism 18. An axial bore 20 passes through the body 12 and has varying diameters. At a proximal end 22 of the body 12 a first portion 24 of the bore 20 has a relatively large diameter to accommodate the spring 16 which is coiled about the piston 14 within the first portion 24. Intermediate portion 26 of the bore 20 has an intermediate diameter closely matched to the diameter of the piston 14.

At a distal end 28 of the body 12 a distal portion 30 of the bore 20 has a narrow diameter to accommodate a hardened setting pin 32 which projects axially from a distal end 34 of the piston 14. Preferably, the setting pin 32 is an integral part of the piston 14, but can alternatively be a separate piece affixed to the piston 14.

The spring 16 is caged between a flange or retaining clip 36 about the piston 14, and a washer 38 and retaining clip 40 at the body proximal end 22. The piston 14 passes outwardly of the body 12 through the washer 38 and retaining clip 14.

At a proximal end 42 of the piston 14 a handle 44 is provided for manual retraction of the piston 14. The proximal half of the body 12 is provided with flutes 46 for enhancing gripability and an axial flange 48 is provided near the body distal end 28 also to enhance gripability and maneuverability of the rivet applier 10. A flat 49 on the flange 48 inhibits rotation of the rivet applier 10, thereby reducing the

likelihood that it will roll off of a surface upon which it is placed. The body distal end 28 tapers to a narrow tip 50 to allow more precise direction of the instrument 10. The set pin 32 is fixed within a coaxial bore 52 in the piston distal end 34.

A circumferencial groove 54 surrounds the piston 14 near its distal end 34. A radial bore 56 passes into the body 12 adjacent the groove 54 and extends beyond the bore 20 but does not completely penetrate the body 12. Turning also to FIG. 3 the release mechanism 18 comprises a release button 58 received within the bore 56 and a the coil spring 60 between an end of the bore 56 and the button 58 which biases the button outwardly of the bore 56. The button 58 has a radial bore 62 through which passes the piston 14. A radial flange 64 within the bore 62 is adapted to engage the circumferential groove 54 on the piston 14.

When the handle 44 is retracted, causing the piston 14 to retract proximally, the flange 64 rides over the surface of the piston 14 until it encounters the circumferential groove 54 into which the spring 60 causes the flange 64 to slip. This action locks the piston 14 in a retracted position as its distal motion is restrained by the abutment of the flange 64 and groove 54. Inward pressure applied to the button 58 causes the flange 64 to disengage from the circumferential groove 54 and allows the spring 16 to drive the piston 14 forward or distally. This causes the setting pin 32 to move distally to a position flush with the distal end of the body 12.

FIGS. 4 and 5 illustrate a rivet 66 for use with the instrument 10. The rivet 66 comprises a round head 68 from which extends axially 3 leaves 70. A cylindrical plug 72

extends axially from the head 68 in the opposite direction and is frangible connected to the head 68 through a frangible connection 74. The surfaces of the leaves 70 are curved so that the combination of the three leaves 70 provides an overall tubular configuration. Application of force in the axial direction applied to the plug 72 breaks its frangible connection 74 with the head 68 and allows it to drive axially into a position between the leaves 70 thus causing the leaves 70 to spread.

FIG. 6 shows a cranial plate 76 for placement on a skull of an patient, either human or animal (not shown). It comprises a flat planar body 78 having a plurality of circular extensions 80 therefrom, each of which has a countersunk bore 82 therethrough. A tag 84 extends from the plate 76 and serves several functions. The tag 84 may contain model number, size, material, date and other pertinent information as well as showing which side of the plate 76 is to face upwards away from the patient's skull (not shown). It also provides a purchase location for a user's hand to hold and manipulate the plate 76 during placement. A frangible connection 86 between the tag 84 and the remainder of the plate 76 allows easy removal of the tag 84 from the plate 76 after placement of the plate 76. Many other configurations of plates will be apparent to those of skill in the art.

Turning to FIGS. 7 to 10, the rivets 66 are disposed for use in a tray 88. The tray 88 comprises a base 90 having a downwardly extending peripheral wall 92 and a plurality of wells 94 therein. Preferably, the wells 94 penetrate the base 90. A plurality of the rivets 66 reside within the plurality of the wells 94 with their plugs 72 facing upwardly out of the wells 94. A film cover 96 adheres to the base 90 over at least the area of the base 90 comprising the wells 92 to hold

the rivets 66 within the wells 92. The film cover 96 preferably has slits 97, scorings or some other weakness at each of the wells 92 to allow access to the rivets 66 through the film cover 96 by the instrument 10 (not shown in FIGS. 8 to 10), although a suitable material allowing access therethrough without slits or the like may be employed.

FIG. 11 illustrates the distal tip 50 of the instrument body 12. It comprises at least one axial slit 98 extending proximally from the distal end 28 and terminating in an aperture 100. A chamfer 102 is also provided at the distal end of the bore 20. In one preferred embodiment, the plugs 72 of the rivets 66 (FIG. 4) have an outside diameter of 0.0590 inches (1.50 mm), the bore distal portion 30 has an inside diameter of .0595 inches (15.1 mm) and the outside diameter of the tip 50 is 0.140 inches (3.56 mm). The slit 98 allows the material of the tip 50 to contract slightly thus reducing the effective internal diameter of the bore distal portion 30 and the aperture 100 reduces stress risers during flexing.

Preferably the rivet 66 and plate 76 are formed of a bioabsorbable material such as a polylactide, such as an 85:15 (mol/mol) poly(lactide-co-glycolide) copolymer. More preferably, the rivet 66 is formed of PLLA and the plates are formed of 50/50 D, LPLA blended with 95/5 PCL/PDO in a 91:9 ratio as more fully described in US Patents Nos. 5,641,501 and 5,705,181, incorporated herein by reference. Preferably the instrument body 12 is formed of a sturdy material such as stainless steel, however, many other materials, including polymers, would be suitable. Preferably, the instrument body 12 weighs considerably more than the piston 14 so as to minimize kick-back as the piston 14 is released. The setting pin 32, and especially if the setting pin 32 and piston 14 are integral, is preferably formed of a hardened steel or

stainless steel, but of course many other hardy materials would be suitable for such service. The tray 88 preferably is formed of a suitable polymer, but can also be formed of other materials.

5

To use the instrument 10, a user grasps the handle 42 and retracts the piston 14 until the flange 64 of the release mechanism 18 engages the annular groove 54 of the piston 14 and holds the piston 14 in a retracted position. The tip 50 of the instrument 10 is inserted through one of the slits 97 to capture the plug 72 of one of the rivets 66 within the bore distal portion 30. The chamfer 102 eases entry of the plug 72 into the bore distal portion 30 and contraction of the tip 50 due to the slit 98 helps the tip 50 grip the plug 72. The rivet 66 is then placed through one of the plate apertures 82 and into a hole in the skull (not shown) and the rivet applier 10 is held thereagainst with some force, say 2 pounds force. Pressing the button 58 releases the engagement of the piston 14 and flange 64 allowing the setting pin 32 to move distally to push against the plug 72 breaking its frangible connection to the head 68 and driving it between the leaves 70 thereby spreading the leaves and setting the rivet 66.

FIGS. 12 and 13 illustrate a bone drill 110 which provides a simple and elegant solution to the problem of centering and boring holes in a patient's skull into which the rivets 66 (not shown in FIG. 12) are received when applying the cranial plate 76 (also not shown in FIG. 12). The drill 110 comprises an elongated drill bit 112 having a proximal end 114 with an attachment surface 116 for attachment to a drill chuck (not shown). Any appropriate attachment surface can be substituted therefor. For instance, a two-piece cap (not shown) can be employed which fits into the tube instead of using a right and left half as shown. A distal end 118 of the

drill bit 112 carries helical cutting edges 120, but other forms of cutting surfaces as appropriate can be substituted therefor. A first radial flange 122 extends radially outwardly from the drill bit 112 and a second larger radial flange 124 extends radially outwardly from the drill bit 112 proximal of the first radial flange 122. A pair of windows 123 allow debris from the drilling to exit the drill 110 and are arranged so as to release the debris before it can reach and possibly interfere with operation of the spring 140.

A tubular housing 126 having an axial bore 128 therethrough coaxially receives the drill bit 112 through the axial bore 128. A proximal end 130 of the housing 126 abuts the second radial flange 124 and thereby limits distal movement of the drill bit 112 through the housing 126. A first diameter 132 of the bore 128 at the housing proximal end 130 closely matches the diameter of the drill bit 112 for sliding engagement. A central diameter 134 of the bore 128 closely matches the diameter of the first radial flange 122 for sliding engagement. A distal diameter 136 of the bore 128 closely matches the diameter of the drill bit 112 for sliding engagement, and the change in diameter of the bore 128 between the central diameter 134 and distal diameter 136 forms a radial abutment 138. A coil spring 140 encircles the drill bit 112 and operates between the abutment 138 and the first radial flange 122 to urge the housing distally along the drill bit 112.

A distal end 142 of the housing 126 carries a chamfer 144 of matching angle to the chamfer of the holes 82 in the cranial plate 76 (see FIG. 6). By pressing the distal end 142 into the chamfered hold 82 the drill bit 112 is centered within the hole 82 allowing accurate drilling. Abutment of the second radial flange 124 and the housing proximal end 130

limits travel of the drill bit 112 out of the housing 126 and thus limits the depth of a hole created by the drill bit 112.

While the invention has been described with regard
5 to a particular embodiment thereof, those skilled in the art will understand, of course, that the invention is not limited thereto since modifications can be made by those skilled in the art, particularly in light of the foregoing teachings. Reasonable variation and modification are possible within the
10 foregoing disclosure of the invention without the departing from the spirit of the invention.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2